



Overview

Model Name	APC Back-UPS 500, 230V without auto shutdown software, ASEAN
Includes	Qty 2 - Detachable 1.8 m IEC power cords , User Manual , Warranty card
Standard Lead Time	Usually in Stock
Product Distribution	Chile , Indonesia , Malaysia , Myanmar , Paraguay , Peru , Philippines , Singapore , Sri Lanka , Thailand , Uruguay , Viet Nam

Output

Output Power Capacity	300 Watts / 500 VA
Max Configurable Power (Watts)	300 Watts / 500 VA
Nominal Output Voltage	230V
Output Frequency (sync to mains)	47 - 63 Hz
Output Frequency (sync to mains)	Line Interactive
Waveform Type	Stepped approximation to a sinewave
Output Connections	(3) IEC 320 C13 (Battery Backup)

Input

Nominal Input Voltage	230V
Input Frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input Connections	IEC-320 C14
Cord Length	1.83 meters

Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	10 hour(s)
Replacement Battery	APCRBC125
RBC Quantity	1

Communications & Management

Audible Alarm	Alarm when on battery : distinctive low battery alarm
---------------	---

Surge Protection and Filtering

Surge energy rating	240 Joules
---------------------	------------

Physical

Maximum Height	185.0 mm
Maximum Width	115.0 mm
Maximum Depth	213.0 mm
Net Weight	4.91 kg
Shipping Weight	5.5 kg
Shipping Height	257.0 mm
Shipping Width	190.0 mm
Shipping Depth	291.0 mm
Master Carton Units	1.0
Color	Black
SCC Codes	0073130426979 3
Units per Pallet	60.0

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000 meters
Audible noise at 1 meter from surface of unit	0.000 dB

Conformance

Standard warranty	2 years repair or replace
-------------------	---------------------------

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs