

## **1200Mbps Dual Band Ceiling AP**

# NC-AC44AP(P)



#### **Features**:

- Wireless N up to 300Mbps, 867Mbps at 5.8GHz
- > 800mw high power for better wireless coverage
- Support DC 12V/1.5A
- Support 802.3at PoE [P version]
- Multi-wireless modes to expand the wireless network: Repeater, Gateway, AP and WISP

1

- Multiple SSID up to 8
- > 802.1Q VLAN and Access Control System supported
- Support Watch Dog, Schedule Reboot, Multi SSID

www.nc-link.cn



## **4** Description

NC-AC44AP(P) is a high power dual band Ceiling Mount Access Point and it is dedicated to big office, hotel, mart,cafe, media room and so on, and it provides a long distance wireless network and good coverage for the large dimensional room.

With PoE technology, providing a compact solution that fits nicely into a situation where electrical outlet is unavailable or hard to reach for specific areas

NC-AC44AP(P) is compatible with 802.11b/g/n/ac devices and provides the wireless transfer speed up to 1200Mbps, offering a better performance on online gaming, video streaming and so on.With many management functions, it is more convenient for users to use.

## Specification

Wireless	
Standards	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n IEEE 802.3at (P version)
Flash & SDRAM	16MB, 128MB
Signal Rate	Up to 1200Mbps 2.4GHz: 300Mbps 5.8GHz: 867Mbps
Frequency Range	2.4-2.4835GHz 5.15GHz-5.825GHz
Transmit Power	29dBm(MAX) 800mW
Data Transfer Rates	802.11ac: 80MHZ(867Mbps) 802.11n: 40MHz (300Mbps, 270Mbps, 240Mbps, 180Mbps, 120Mbps, 90Mbps, 60Mbps, 30Mbps) 20MHz (144Mbps, 130Mbps, 115Mbps, 86Mbps, 57Mbps, 43Mbps, 28Mbps, 115Mbps) (Auto-Sense) 801.11g: (54Mbps, 48Mbps, 36Mbps, 24Mbps, 18Mbps, 12Mbps, 11Mbps, 9Mbps, 6Mbps) 802.11b: (11Mbps, 9Mbps, 6Mbps, 5.5Mbps, 2Mbps, 1Mbps)

2



///////////////////////////////////////	
Wireless Modes	Repeater, Gateway, AP, WISP
Wireless Security	64/128-bit WEP,
	WPA-PSK/WPA2-PSK (TKIP/AES)
	SSID Broadcast Enable/Disable
	Wireless MAC Filtering

Hardware	
Standards	IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX IEEE 802.3at(P version)
Interfaces	1 * 10/100/1000M Auto MDI/MDIX RJ45 WAN port 1 * 10/100/1000M Auto MDI/MDIX RJ45 LAN port
Buttons	Reset
Antenna	Build in 4*6dBi Antenna
Power Supply	DC12V/1.5A; PoE 48V
Dimensions (L x W x H )	189*385mm
Weight	400 g

Software	
WAN Type	DHCP(Dynamic IP), PPPoE, Static IP, WISP
Port Forwarding	Virtual Servers, Port Triggering, UPnP, DMZ, FTP Private Port
QoS	WMM, Bandwidth Control
Access Control	IP/MAC/Domain filtering
VPN Pass-through	PPTP, L2TP, IPSEC
Others	DDNS, Static Routing, WOL, Remote Management, Firmware upgrade

Others	
Environment	Operating Temperature: 0℃~40℃ Storage Temperature: -40℃~70℃
	Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing
Package	1 * 1200Mbps Dual Band Ceiling AP 1 * Ethernet Cable 1* Wall mount accessory





