



Overview

Model Name	APC Back-UPS 625VA, 230V, AVR, Floor, Universal Sockets
Includes	Qty 1 - Detachable 2.0 m NEMA 5-15P to IEC C13 power cord , User Manual
Standard Lead Time	Usually in Stock
Product Distribution	Cambodia , Indonesia , Malaysia , Myanmar , Nepal , Philippines , Singapore , Thailand , Viet Nam

Output

Output Power Capacity	325 Watts / 625 VA
Max Configurable Power (Watts)	325 Watts / 625 VA
Nominal Output Voltage	230V
Nominal Output Voltage	Line Interactive
Waveform Type	Square wave
Output Connections	(3) Universal Receptacle (Battery Backup)

Input

Nominal Input Voltage	230V
Input Frequency	45 - 65 Hz
Input Connections	IEC-320 C14
Cord Length	1.22 meters
Input voltage range for main operations	151 - 299 V
Maximum Input Current	3 A
Input Breaker Capacity	7 A
Type of Input Protection Required	3-pole breaker

Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Included Battery Modules	1
Typical recharge time	6 hour(s)
Replacement Battery	APCRBC110

Surge Protection and Filtering

Surge energy rating	273 Joules
---------------------	------------

Physical

Maximum Height	279.0 mm
Maximum Width	160.0 mm
Maximum Depth	89.0 mm
Net Weight	5.0 kg
Shipping Weight	5.2 kg
Shipping Height	399.0 mm
Shipping Width	215.0 mm
Shipping Depth	128.0 mm
Master Carton Units	1.0
Color	Black
SCC Codes	1073130430817 8
Units per Pallet	100.0

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Storage Temperature	-15 - 40 °C
Storage Relative Humidity	0 - 95 %
Audible noise at 1 meter from surface of unit	45.000 dB

Conformance

Standard warranty	2 years repair or replace
Equipment protection policy	No EPP for ASEAN

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs