

เอกสารข้อมูลผลิตภัณฑ์

ข้อมูลจำเพาะ



APC Back-UPS Pro, 1200VA/
720W, Tower, 230V, 8x IEC C13
outlets, Sine Wave, AVR, USB
Type A + C ports, LCD, User
Replaceable Battery

BR1200SI

Overview

Lead Time Usually in Stock

Main

Main Input Voltage	230 V
Rated Power In W	720 W
Rated Power In Va	1200 VA
Product Or Component Type	Uninterruptible power supply (UPS)
Input Connection Type	IEC 60320 C13
Output Connection Type	6 IEC 60320 C13 2 IEC 60320 C13 surge
Battery Type	Lead-acid battery

Batteries & Runtime

รันไทม์	View Runtime Graph
ประสิทธิภาพ	View Efficiency Graph
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Battery Recharge Time	16 h
Number Of Battery Replacement Quantity	1
Battery Voltage	24 V
Battery Capacity	9.0 Ah
Battery Charger Power	13 W rated
Battery Life	3...5 year(s)
Replacement Battery	APCRBC161
Extended Runtime	0

General

Provided Equipment	user manual USB cable
Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0

Redundant	No
-----------	----

Physical

Colour	Black
Height	26 cm
Width	10 cm
Depth	36.8 cm
Net Weight	11.7 kg
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	No

Input

Network Frequency	50/60 Hz +/- 3 Hz auto-sensing
Input Voltage Limits	176...294 V
Maximum Input Current	10 A
Switching Current Capacity	10 A

Output

Maximum Configurable Power In W	720 W
Output Frequency	50/60 Hz +/- 1 Hz sync to mains
Ups Type	Line interactive
Maximum Configurable Power In Va	1200 VA

Conformance

Product Certifications	A-Tick C-Tick CE EAC RCM TISI
Marking	GS Mark
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 % non-condensing
Operating Altitude	0...10000 ft
Ambient Air Temperature For Storage	-15...45 °C
Storage Relative Humidity	0...95 % non-condensing
Storage Altitude	0.00...15240.00 m
Acoustic Level	45 dBA

Heat Dissipation	16 Btu/h
------------------	----------

Communications & Management

Control Panel	Multifunction LCD status and control console
---------------	--

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
-------	--

Surge Protection and Filtering

Surge Energy Rate	509 J
-------------------	-------

Noise Suppression	Full time multi-pole noise filtering : 10% of IEEE surge let-through : zero clamping response time: instantaneous
-------------------	---

Packing Units

Unit Type Of Package 1	PCE
------------------------	-----

Number Of Units In Package 1	1
------------------------------	---

Package 1 Height	35.9 cm
------------------	---------

Package 1 Width	48.2 cm
-----------------	---------

Package 1 Length	22.3 cm
------------------	---------

Package 1 Weight	13.35 kg
------------------	----------

Scs14	10731304346897
-------	----------------

Contractual warranty

Warranty	2 years repair or replace, 3 years repair or replace for European Union countries
----------	---

ความยั่งยืน

ฉลาก **Green Premium™** เป็นความมุ่งมั่นของSchneider Electric ในการส่งมอบผลิตภัณฑ์ที่มีประสิทธิภาพด้านสิ่งแวดล้อมที่ดีที่สุด Green Premium ให้คำมั่นว่าจะปฏิบัติตามกฎระเบียบล่าสุด ความโปร่งใสต่อผลกระทบด้านสิ่งแวดล้อม รวมถึงผลิตภัณฑ์หมุนเวียนและ CO₂ ต่ำ

คู่มือการประเมินความยั่งยืนของผลิตภัณฑ์เป็นเอกสารวิจัยที่ช่วยชี้แจงมาตรฐานฉลากสิ่งแวดล้อมทั่วโลกและวิธีการตีความการประ



ประหยัดพลังงาน Take-back ความโปร่งใส RoHS/REACH

ประสิทธิภาพทรัพยากร

- ✓ Energy Efficient Product
- ✓ Take-Back Program Available

ประสิทธิภาพด้านสุขภาพ

- ✓ Mercury Free
- ✓ Rohs Exemption Information [Yes](#)

ใบรับรองและมาตรฐาน

Reach Regulation	REACH Declaration
Eu Rohs Directive	Compliant with Exemptions
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information