

เอกสารข้อมูลผลิตภัณฑ์

ข้อมูลจำเพาะ



APC Back-UPS Pro, 900VA/540W, Tower, 230V, 6x IEC C13 outlets, AVR, LCD, User Replaceable Battery

BR900MI

Overview

Lead Time Usually in Stock

Main

Main Input Voltage 230 V

Rated Power In W 540 W

Rated Power In Va 900 VA

Product Or Component Type Uninterruptible power supply (UPS)

Input Connection Type IEC 60320 C13

Output Connection Type 6 IEC 60320 C13

Battery Type Lead-acid battery

Batteries & Runtime

รันไทม์ [View Runtime Graph](#)

ประสิทธิภาพ [View Efficiency Graph](#)

Number Of Battery Filled Slots 0

Number Of Battery Free Slots 0

Battery Recharge Time 12 h

Number Of Battery Replacement Quantity 1

Battery Voltage 12 V

Battery Capacity 9.4 Ah

Battery Charger Power 11 W rated

Battery Life 3...5 year(s)

Replacement Battery [APCRBC164](#)

Extended Runtime 0

General

Provided Equipment user manual
USB cable

Number Of Power Module Free Slots 0

Number Of Power Module Filled Slots 0

Redundant No

Physical

Height	19 cm
Width	9.1 cm
Depth	31 cm
Net Weight	7.1 kg
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	No

Input

Network Frequency	50/60 Hz +/- 3 Hz auto-sensing
Input Voltage Limits	176...294 V
Maximum Input Current	10 A
Switching Current Capacity	10 A

Output

Maximum Configurable Power In W	540 W
Output Frequency	50/60 Hz +/- 1 Hz sync to mains
Ups Type	Line interactive
Wave Type	Stepped approximation to a sinewave
Maximum Configurable Power In Va	900 VA
Transfer Time	10 ms typical : 12 ms maximum

Conformance

Product Certifications	A-Tick C-Tick CE EAC RCM TISI
Marking	GS Mark
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 %
Operating Altitude	0...10000 ft
Ambient Air Temperature For Storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage Altitude	0.00...15240.00 m
Acoustic Level	45 dBA
Heat Dissipation	16.4 Btu/h

Communications & Management

Control Panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Noise Suppression	Full time multi-pole noise filtering : 10% of IEEE surge let-through : zero clamping response time: instantaneous
-------------------	---

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	25.5 cm
Package 1 Width	14.3 cm
Package 1 Length	44 cm
Package 1 Weight	8 kg
Sccl4	10731304346941

Contractual warranty

Warranty	2 years repair or replace, 3 years repair or replace for European Union countries
----------	---

ความยั่งยืน

ฉลาก **Green Premium™** เป็นความมุ่งมั่นของSchneider Electric ในการส่งมอบผลิตภัณฑ์ที่มีประสิทธิภาพด้านสิ่งแวดล้อมที่ดีที่สุด Green Premium ให้คำมั่นว่าจะปฏิบัติตามกฎระเบียบล่าสุด ความโปร่งใสต่อผลกระทบด้านสิ่งแวดล้อม รวมถึงผลิตภัณฑ์หมุนเวียนและ CO₂ ต่ำ

คู่มือการประเมินความยั่งยืนของผลิตภัณฑ์เป็นเอกสารวิจัยที่ช่วยชี้แจงมาตรฐานฉลากสิ่งแวดล้อมทั่วโลกและวิธีการตีความการประ



ประหยัดพลังงาน Take-back ความโปร่งใส RoHS/REACH

ประสิทธิภาพทรัพยากร

- ✓ Energy Efficient Product
- ✓ Take-Back Program Available

ประสิทธิภาพด้านสุขภาพ

- ✓ Mercury Free
- ✓ Rohs Exemption Information [Yes](#)

ใบรับรองและมาตรฐาน

Reach Regulation	REACH Declaration
Eu Rohs Directive	Compliant with Exemptions
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information