

Wireless ADSL Router

With Firewall Protection/QoS Control

- Integrated ADSL, 802.11g Wireless LAN & 4-Port Switch
- High-Speed ADSL2/2+ Connection
- DoS & SPI Firewall Protection
- QoS & SNMP Management Support

FEATURES

Wireless ADSL Router

- Built-in ADSL Interface
- Built-in 802.11g WLAN Up to 54Mbps Speed
- Integrated 4-Port Ethernet Switch

High-Speed ADSL Access

- ADSL: G.992.1 (G.dmt), G.992.2 (G.lite) Annex A, G.994.1 (G.hs), Multi-mode, ANSI T1.413 Issue 2
- ADSL2: G.992.3 (G.dmt.bis) Annex A/L/M, G.992.4 (G.lite.bis) Annex A
- ADSL2+: G.992.5 Annex A/L/M

Firewall/Access Security

- DoS Attack Prevention
- Stateful Packet Inspection (SPI)
- IP/MAC-Based Packet Filtering
- Port-Based VLAN

QoS/Bandwidth Control

- Traffic Prioritization With 4 Priority Queues
- IGMP Snooping Multicast

Easy Setup/Flexible Management

- Dynamic Domain Name System (DDNS)
- Universal Plug and Play (UPnP) Compliant
- Quick Installation Wizard
- Web-Based GUI for Local/Remote Management
- SNMP Management

Remote Management

- TR-069 (optional)

The DSL-2640T wireless ADSL router is a versatile, high-speed remote router for home and the small office. With integrated ADSL2/2+ supporting up to 24Mbps download speed, firewall protection, Quality of Service (QoS), 802.11g wireless LAN and 4 Ethernet switch ports, this router provides all the functions that a home or small office needs to establish a secure and high-speed remote link to the outside world.

High-Speed ADSL Connection. The DSL-2640T features the latest ADSL2/ADSL2+ standards, providing speeds of up to 24Mbps downstream and 1Mbps upstream (ADSL2+), or 12Mbps downstream and 1Mbps upstream (ADSL2). This router auto-senses the connection type and auto-negotiates the best modulation scheme, using the G.hs (handshake) protocol.

Ready Wireless LAN & Ethernet Connection for Workgroup. The DSL-2640T provides an integrated 802.11g WLAN interface supporting wireless speeds of up to 54Mbps and interoperability with 802.11b wireless devices on the 2.4GHz frequency band. It also provides four 10/100Mbps Ethernet switch ports for ready workstations connection. These built-in functions save you the cost and trouble of installing a separate wireless access point and an Ethernet switch.

Firewall Protection. The router provides firewall security using Stateful Packet Inspection (SPI) and hacker attack logging for Denial of Service (DoS) attack protection. SPI inspects the contents of all incoming packet headers before deciding what packets are allowed to pass through. Access control is provided with packet filtering based on port and source/destination MAC/IP addresses. With Virtual Server Mapping, the router can be set to allow separate FTP, Web, and multiple games to share the same Internet-visible IP address while still protecting your servers and workstations from hackers. You can configure any of the built-in LAN ports of the router to function as a DMZ port. VPN pass-through is provided to let mobile users access files and mail from offices to work at home without having to use complex VPN client software.

Quality of Service Features. The DSL-2640T supports 4 priority queues to enable a group of home or office users to experience the benefit of smooth network connection of inbound and outbound data without concern of traffic congestion. This QoS support allows you to enjoy high ADSL transmission for applications such as VoIP, multimedia and on-line games over the Internet.



Technical Specifications

Hardware

Interfaces

- 1 RJ-11 ADSL port
- 4 RJ-45 10/100BASE-TX Fast Ethernet LAN switch ports with auto MDI/MDIX
- Built-in WLAN
- Factory reset button

Wireless LAN

- IEEE 802.11g standard
- Wireless speed: up to 54Mbps
- Frequency range: 2.4 GHz to 2.484 GHz
- 64/128 bits WEP data encryption
- WPA (Wi-Fi Protected Access), WPA2 security
- Point-to-Point and Point-to-Multi-point Wireless Bridging
- 802.11e Wireless QoS (WMM/WME)

ADSL

Standards

- ADSL standards: Multi-mode, ANSI T1.413 Issue 2, ITU G.992.1 (G.dmt) Annex A, ITU G.992.2 (G.lite) Annex A, ITU G.994.1 (G.hs)
- ADSL2 standards: ITU G.992.3 (G.dmt.bis) Annex A/L/M, ITU G.992.4 (G.lite.bis) Annex A
- ADSL2+ standards: ITU G.992.5 Annex A/L/M

Data Rates

- G.dmt: 8Mbps downstream, 832Kbps upstream
- G.lite: 1.5Mbps downstream, 512Kbps upstream
- ADSL2: 12Mbps downstream, 1Mbps upstream
- ADSL2+: 24Mbps downstream, 1Mbps upstream

ATM & PPP Protocols

- ATM Adaptation Layer Type 5 (AAL5)
- Bridged or routed Ethernet encapsulation
- VC and LLC based multiplexing
- PPP over Ethernet (PPPoE)
- PPP over ATM (RFC 2364)
- Classical IP over ATM (RFC 1577)
- OAM F4/F5

Router

Network Protocols & Features

- NAT, Static Routing, RIP v.1, v2
- Universal Plug and Play (UPnP) Compliant
- Dynamic Domain Name System (DDNS)
- Virtual Server & DMZ
- SNTP, DNS proxy and IGMP proxy

Firewall/Access Security

- Built-in NAT firewall
- Stateful Packet Inspection (SPI)
- DoS attacks prevention (IP Spoofing, Land Attack, Smurf Attack, Ping of Death, TCP SYN flooding)
- Packet filtering based on port, source IP address, destination IP address, MAC address (ICMP/TCP/UDP)

Virtual Private Network (VPN)

PPTP/IPSec pass-through

Configuration/Management

- Quick Installation Wizard
- Web-based GUI for remote/local management
- Firmware upgrade, configuration data upload/download via Web-based GUI

- Telnet server for remote/local management
- Syslog monitoring
- SNMP v.1, v2c support with built-in MIB-II (RFC 1213)
- DHCP server/client/relay

QoS Control

- LAN to WAN traffic prioritization/bandwidth management
- 802.1p traffic prioritization (4 queues)

Security/Bandwidth Management

- IGMP Snooping with 32 Multicast groups
- PVC/VLAN port mapping (4 VLANs)
- Bandwidth management based-on IP protocol, port number, MAC address

Physical & Environmental

Power Input

Through 12VAC 1.2A external power adapter

Dimensions

142 x 109 x 31 mm

Weight

239.4 grams

Operating Temperature

0° to 40°C

Storage Temperature

-20° to 70°C

Operating Humidity

5% to 95% non-condensing

Emission (EMC/EMI)

- FCC Part 15 Class B
- CE (EN55022/EN55024/EN300 328/EN301 489)

Safety

- CSA
- LVD

Wi-Fi Certification



D-Link Worldwide Offices

U.S.A	TEL: 1-800-326-1688	FAX: 1-866-743-4905	Bulgaria	TEL: 359 2 958 22 42	FAX: 359 2 958 65 57
Canada	TEL: 1-905-8295033	FAX: 1-905-8295223	Romania	TEL: 40(0)21 320 23 05	FAX: 40(0)21 320 23 07
Europe (U. K.)	TEL: 44-(0)20-8955-9000	FAX: 44-(0)20-8955-9002	Singapore	TEL: 65-6774-6233	FAX: 65-6774-63225
Germany	TEL: 49-(0)6196-77990	FAX: 49-(0)6196-7799300	Australia	TEL: 61-2-8899-1800	FAX: 61-2-8899-1868
France	TEL: 33 (0)1 30 23 86 88	FAX: 33 (0)1 30 23 86 89	India	TEL: 91-22-2652 6696	FAX: 91-22-2652 8914
Netherlands	TEL: 31-(0)10-282-1445	FAX: 31-(0)10-282-1331	Middle East (Dubai)	TEL: 971-4-391-6480	FAX: 971-4-390-8881
Belgium & Luxembourg	TEL: 32(0)2 517 7111	FAX: 32(0)2 517 6500	Egypt	TEL: 202-291-9035	FAX: 202-291-9051
Switzerland	TEL: 41 (0)1 832 11 00	FAX: 41 (0)1 832 11 01	Turkey	TEL: 90-212-289-5659	FAX: 90-212-289-7606
Austria	TEL: 43 (0)1 240 27 270	FAX: 43 (0)1 240 27 271	Iran	TEL: 90-212-289-5659	FAX: 90-212-289-7606
Sweden	TEL: 46-(0)8 564 619 00	FAX: 46-(0)8 564 619 01	Pakistan	TEL: 92-21-454-8158	FAX: 92-21-453-5103
Denmark	TEL: 45-43-969040	FAX: 45-43-424347	Israel	TEL: 972-9-9715700	FAX: 972-9-9715601
Norway	TEL: 47 99 300 100	FAX: 47 22 30 90 85	Latin America	TEL: 56-2-5838-950	FAX: 56-2-5838-953
Finland	TEL: 358-10 309 8840	FAX: 358-10 309 8841	Brazil	TEL: 55-11-2185-9300	FAX: 55-11-2185-9322
Italy	TEL: 39-02-2900-0676	FAX: 39-02-2900-1723	South Africa	TEL: 27-12-665-2165	FAX: 27-12-665-2186
Spain	TEL: 34 93 409 0770	FAX: 34 93 491 0795	Russia	TEL: 7-495-744-0099	FAX: 7-495-744-0099
Portugal	TEL: 351 21 8688493	FAX: 351 21 8622492	Japan	TEL: 81-3-5781-0963	FAX: 81-3-5781-0965
Greece	TEL: 30 210 9914 512	FAX: 30 210 9916902	Korea	TEL: 82-2-890-5498	FAX: 82-2-890-5497
Czech Republic	TEL: 420 224 247 500	FAX: 420 224 234 967	China	TEL: 86-10-58635800	FAX: 86-10-58635799
Hungary	TEL: 36 (0)1 461 30 00	FAX: 36 (0)1 461 30 04	Taiwan	TEL: 886-2-6600-0123	FAX: 886-2-6600-3939
Poland	TEL: 48 (0)22 583 92 75	FAX: 48 (0)22 583 92 76	Headquarters	TEL: 886-2-6600-0123	FAX: 886-2-6600-9898