

EWS550AP

Dual Band AC1300

Indoor Wall Plate Access Point

The edge 802.11ac built-in high performance Access Point with MU-MIMO technology for high-density use on multiple applications.

EnGenius Wireless Management Access Point solution is designed for deploying on the versatile indoor application. To meet today's requirement on varied net-working environment, EnGenius would like to provide the solution as flexible, robust and effective as the organization they desire.

The state-of-the-art 802.11ac and MU-MIMO technology brings revolutionary connecting speed and bandwidth for diversity of multimedia applications. EWS550AP equips with two powerful RF interfaces that support up to 867 Mbps in 5GHz frequency band and 400 Mbps in 2.4GHz frequency band (with 4ss/VHT40 clients).



Features

- > Built-in Turbo Engine solution with a Quadcore powerful chipset solution to process multiple tasks for driving and enhancing performance effectively.
- Dual radio 2x2 802.11 ac/a/b/g/n Access Point with multi-user MIMO (MU-MIMO)
- Easy-to-deploy, lowers install costs for hotel, guest rooms, dorms & classrooms
- Sleek, low profile design mounts onto a standard J-box
- > High powered amplifiers to improve the wireless coverage and uses a special radio frequency pattern to increase its receiver sensitivity for improved performance.
- Support 802.11ac Wave 2.0 technology to enhance overall bandwidth and speed to wireless client devices.
- > 360° omni-directional antennas to achieve comprehensive coverage for networking client devices under a pervasive environment.
- Compliance with 802.3af 48V PoE Input for flexible installation over 100 meters (328 feet)
- > Systemic and distributed management over EnGenius ezMaster and EWS Management switch without licensing or subscription fee.

Wireless Management solution is ideal for deployment in these venues:

- > Education
- > Managed Service Providers
- > Retail
- > Entertainment

- > Multiple Dwelling Units
- > Hospitality
- > Residential
- > Dormitory

- > Professional A/V
- > Healthcare
- > Luxury Homes & Estates
- > Class room

Provide Consistent Performance

Designed by EnGenius could provide the powerful RF interfaces to assure the reliability of signal strength and sensitivity in a pervasive environment. The optimist interfaces will provide the evenly coverage to assist users to reduce dead spots in their WLAN and boost received signal quality to deliver the best 1.26Gbps air performance to wireless client devices.

Carry multimedia content over MU-MIMO Transmit Beam-forming technology.

Be a prior AC1300 solution, EWS550AP are not only built in powerful RF interfaces, but it also features advanced Multi-Users Multiple input Multiple output (MU-MIMO) and Transmit beamforming (TxBF) technologies.

The significant improvement on 802.11ac wave 2.0 is MU-MIMO technology, which enhances a dramatic break-through in the performance and flexible transmission to wireless client devices. MU-MIMO allows multiple spatial streams to be allocated to different clients simultaneously, increasing totally throughput, reduce latency, capacity of the WLAN system and increase spectral efficiency.

Beamforming is a standard in 802.11ac wave 2.0 which allows Access Points to focus energy of multiple antennas to transmit to a particular client device in that direction of that client. The innovative technology significantly enhances the higher signal-to-noise ratio and greater throughput of that client.

With MU-MIMO and Beamforming technology, EWS550AP advanced Indoor Access Points could bring more traffic to wireless client devices simultaneous over the longer distance and save time for serving other wireless client devices.



Exquisite RF Management to Achieve Optimal Wireless Performance

EnGenius intelligent RF detecting mechanism—Background Scanning, continues to monitor RF movement of an environment and initialize the control of Transmit Power and channel assignment assuring the evenly RF coverage and consistent wireless performance. To assist client devices to get the optimal performance under a pervasive environment, Band Steering automatically steers dual-band capable client devices to the appropriate channel, while prefer 5GHz or band balancing works to maintain a balanced number of clients per Access Point. Configuring multiple Access Points to serve your own devices (BYOD) in enterprise class wireless LAN environment can enable Fast Roaming to reduce roaming delay time and to secure seamless connection on VOIP service when mobile devices move between Access Points.



Securable Portals for different purpose

EnGenius provides **Captive Portal** to differentiate the authority of users on using Internet access. Considering the value added function, administrators offer a securable service to serve client devices including to encrypt over database of an authentication server, customized-branded splash of webpage, simplified logon service, and promoting content and using polices. Administrators can also use **Virtual LAN (VLAN)** with **Guest Network** to isolate each client for avoiding an unnecessary touch, leaking sensitive data, and enhancing Internet security and reliability.

Restrain Wireless Traffic under a Pervasive Environment

To effective manage the usage of each client devices at a LAN topology, **Traffic Shaping** controls the bottle of bandwidth to offer the limited bandwidth for an individual **SSID** or **each client** per Access Point. This constraint offers the constant bandwidth to perform specific applications like VOIP and video streaming fluently and smoothly without air congestion on each client devices.

Comprehensive Network Protection

With EWS Access Points, your network is protected from attacks at multiple level through advanced wireless encryption standards such as Wi-Fi Protected Access (WPA and WPA2) which uses a temporal key integrity protocol (TKIP) and authentication database, IEEE 802.1X with Radius server. EnGenius also offers the advanced encryption standard (AES) to encrypt traffic between Access Points and client devices. EnGenius wireless management system offers advanced mechanism to detect and to prohibit threats over **Rogue AP detection**. Once threats or event are detected, built-in **E-mail Alerts** systems will automatically deliver an e-mail notification for administrators to trigger immediate actions on these networks threats.

Simplified Management and Configuration over ezMaster or EWS Management Switch

EWS-series managed Access Point is designed to work with EWS-series Wireless Management Switch and ezMaster management platform for scalable and flexible wireless management application.

Whether you want to manage a few or 1000+ Access Points and switches on network in different locations with different segment —or 10 to 10,000 concurrent users, the **EnGenius ezMaster platform** makes these management and configuration simplified and intuitively over centralizing bulk configuration, provision and monitoring which is the lower operating and maintenance cost from a local or remote server—or in the cloud.

With the small scope or maximum 50pcs managed requirement, **EWS management switch** can perform auto discovery to search EWS managed Access Points. WLAN administrator can easily use individual or cluster settings to fast deploy numbers of AP with desired settings, saving repetitive configuration tasks.

Via SmartSync Redundancy, if the connection to your ezMaster platform is lost, EWS management switch will automatically store syslog and statistics from the APs. Then, when the connection is re-established, all information will be re-synchronized and sent to ezMaster Management platform. Administrators will not miss any statistics and reports.



Technical Specifications Wireless Managed Wall Plate Access Point

Wireless Radio Specification

Access Point Type:

Indoor, dual radios concurrent, 5GHz 802.11 ac 2x2 MIMO is back-wards compatible with 802.11 a/n mode, 2.4GHz 802.11 n 2x2 MIMO is backwards compatible with 802.11 b/g.

SU-MIMO.

Two(1) spatial stream SU-MIMO for up to 1,267 Mbps wireless data rate to a single wireless client device.

MU-MIMO

Two(1) spatial stream MU-MIMO for up to 867 Mbps wireless data rate to transmit to two(2) MU-MIMO capable wireless client devices simultaneously.

Frequency Radio 2.4GHz: 2400MHz ~ 2835MHz, 5GHz: 5150MHz~5250MHz, 5250MHz~5350MHz, 5470~5725MHz, 5725MH7~5850MH7

Support radios and channels will be varied on the configured regulatory domain.

Supported Radio Technology

802.11b: Direct-sequence spread-spectrum (DSSS) 802.11ac/a/g/n: Orthogonal frequency-division multiplexing (OFDM) 802.11n/ac: 2x2 MIMO with 4 streams 802.11ac supports very high throughput (VHT) - VHT 20/40/80 MHz 802.11n supports high throughput (HT) — HT 20/40 MHz 802.11n supports very high throughput under the 2.4GHz radio –VHT40 MHz (256-QAM) 802.11n/ac packet aggregation: A-MPDU, A-SPDU

Supported Modulation Type

802.11b: BPSK, QPSK, CCK 802.11a/g/n: BPSK, QPSK, 16-QAM, 64-QAM 802.11ac: BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM

Transmit Power (Maximum Value) 2.4GHz: 15dBm 5GHz: 15dBm

Maximum power is limited by regulatory domain

Tx Beamforming (TxBF) Increasing signal reliability and transmitting distance.

Supported data rates (Mbps) 802.11b: 1, 2, 5.5, 11 802.11a/g: 6, 9, 12, 18, 36, 48, 54 802.11n: 6.5 to 300 (MCS0 to MCS15)

802.11ac: 6.5 to 867 (MCS0 to MCS9, NSS=1 to 2)

Power

Maximum Power Consumption

10W

Power Source Power Over Ethernet: Supports 802.3af output when PoE input is 802.3at

Antenna

Integrated Antenna 2.4GHz: 4 .0 dBi 5GHz: 6.0 dBi

Interfaces

Networking Interface

Uplink (Back plate): $1 \times 10/100/1000$ Mbps Ethernet port Client Ports: $3 \times 10/100/1000$ Mbps Ethernet ports -Port 1 is PSE – Provides 802.3af PoE/ Requires 802.3at power source $1 \times 10/100/1000$ Mbps Pass-through port (connectivity provided by backend switch) 1×110 punch down block $2 \times RMS$ pass through port 2 x RJ45 pass through ports

LED Indicators

Display system and wireless transmission status

Reset Button

Convert Access Point to the Factory default or the Users Default

Mounting

Wall Mounting

Assemble a mounting bracket for J-box

Mechanical & Environment

Dimensions W: 4.9" x L: 7.4" x H: 1.0" (12.5 x 18.8 x 2.6 cm)

Weight

0.454 Kg (1.0 lbs)

Operating: Temperature: 0°C~40°C (32°F~104°F) Humidity: 0%~90% typical

Storage:

Temperature: -30°C~70°C (-22°F~158°F) Humidity: 0%~90% typical

Compliance Regulatory

FCC Subpart15 B Subpart C 15.247 Subpart E 15.407

CF EN 301 893 EN 300 328

EN 301 489 1 & 17 EN 50385 EN 55022 (CISPR 22) EN 60601-1-2

R&TTE Directive 1995/5/EC

Low Voltage Directive 72/23/EEC

Technical Specifications Wireless Indoor Access Point

Operating Mode

AP, WDS

Two configuration options broaden the devices' adaptability to your network needs.

Exquisite RF Management

Background Scanning

Regular scanning signal level of an environment to provide parameters for performing Auto Transmit power and auto channel.

Auto Transmit Power

Automatically adjust power level when EWS access points work at an environment.

Auto Channel

Automatically assign a clearly channel to perform RF transmission under a pervasive environment.

Fast Roaming (802.11k)

Collect the parameters of neighborhood Access Points to find the optimal AP.

Band Steering

Steer client devices to a proper frequency band for getting more band-width and speed under an Access Point.

RSSI Threshold

Kick the client which the signal (RSSI) is above the set value from the AP for reducing the interference and optimize the connecting quality.

Optimize Performance

Quality of Service Compliance with IEEE 802.11e standard Prioritizes voice over data for both tagged and untagged traffic Transmit video, voice and data at the same SSID

Power Save Mode

Support U-APSD

Pre-Authentication Compliance with 802.11i & 11x

PMK Caching

Compliance with 802.11i If wireless client devices has authenticated to an access point, it does not perform a full authentication exchange when client devices roaming between access points.

Fast Roaming (802.11r)

Use a Fast Transition key to handover between Access Points

Multicast to Unicast Conversion

Using the IGMP protocol, an access Point delivers high definition content to a large number of clients simultaneously.

Easy to Management

Multiple SSIDs

BSSID support Support 8 SSIDs on both 2.4GHz and 5GHz bands

Captive Portal

Differentiate the authority of users on using Internet access

Guest Network

Isolate each client for avoiding an unnecessary touch, leaking sensitive data, and enhancing Internet security and reliability.

VLAN Tag

Independent VLAN setting can be enable or disable. Any packet that enters the Device without a VLAN tag will have a VLAN tag inserted with a PVID (Ethernet Port VID)

VLAN Per SSID

Integrate VLAN ID with a SSID interface to forward packets over the defined path.

Management VLAN

Feature is enabled with specified VLAN ID, the device will only allow management access with the same specified VLAN ID from remotely location by using protocols such as telnet, SSH, snmp, syslog etc.

Traffic Shaping

Controls the bottle of bandwidth to offer the limited bandwidth for an individual SSID or each client per Access Point.

MAC Address Filtering Filter up to 64 sets MAC addresses per SSID

E-Mail Alert Provides a network monitoring tool for administrators to stay informed the configuration change.

Finger Printing

The value added solution collect information of client devices including name of devices, IP address, MAC address, Operating system version, transmitting and receiving data, and signal level.

Save Configuration as Users Default

Save the customized configuration as default value for different customer demands.

Wi-Fi Scheduler

Perform a regular reboot on access point at assigned schedule Perform it to enable or disable 2.4GHz or 5GHz interface from a period time.

SNMP & MIB

v1/v2c/v3 support MIB I/II, Private MIB CLI supported

RADIUS Accounting Help operators to offload 3G to Wi-Fi seamlessly

Wireless Clients list

Provide the list to display real status of wireless client devices on this Access Point.

Comprehensive Protection

Wireless Encryption Standard

WEP Encryption—64/128/152 bit WPA/WPA2 Enterprise (WPA-EAP using TKIP or AES)

Hide SSID in beacons

Rogue AP Detection Enable the function to detect the fake access points in the environment.

L2 Isolation

Block the communication between the associated clients to communicate with other clients from all hosts on the same subnet.

Client Isolation

Block/Isolate the communication between the associated clients under the same WLAN.

HTTPS

A secure communication protocol can be enabled to allow secure management web access over a computer network.

SSH Tunnel

A secure communication protocol can be enabled to allow secure remote shell access or command execution.

RF Performance Specification Wireless Indoor Access Point

Channel	Data Rate	Transmit Power (Aggregated, dBm)	Receive Sensitivity (Aggregated, dBm)
802.11b 2.4 GHz	1 Mbps	15	-80
	2 Mbps	15	-80
	5.5 Mbps	15	-80
	11 Mbps	15	-76
802.11g 2.4 GHz	6 Mbps	15	-82
	54 Mbps	13	-65
802.11a 5 GHz	6 Mbps	14	-82
	54 Mbps	12	-65
802.11n HT20 2.4 GHz	MCS 0 / 8 / 16 / 24	15	-82
	MCS 7 / 15 / 23 / 31	13	-64
802.11n HT40 2.4 GHz	MCS 0 / 8 / 16 / 24	14	-79
	MCS 7 / 15 / 23 / 31	12	-54
802.11n HT20 5GHz	MCS 0 / 8 / 16 / 24	14	-82
	MCS 7 / 15 / 23 / 31	12	-64
802.11n HT40 5GHz	MCS 0 / 8 / 16 / 24	14	-79
	MCS 7 / 15 / 23 / 31	12	-54
802.11ac VHT20 5GHz	MCS0	14	-82
	MCS9	12	-59
802.11ac VHT40 5GHz	MCS0	14	-79
	MCS9	12	-61
802.11ac VHT80 5GHz	MCS0	14	-76
	MCS9	11	-51

*Maximum RF performance of the hardware provided. Maximum transmit power is limited by local regulatory.

*The supported frequency bands are restricted by local regulatory requirements.

*Transmit power is configured in 1.0dBm increments.

EWS550AP



2.4GHz H-Plane

2.4GHz E-Plane



5GHz H-Plane



5GHz E-Plane



Physical Interfaces



10/100/1000 RJ45 Uplink (PoE In)

	EnGenius	
Standards	802.11ac/a/b/g/n	
Frequency	2.4GHz+5GHz	
Data Rates	400Mbps + 867 Mbps	
Antennas	2.4GHz: 4.0dBi; 5GHz: 6.0dBi	
Physical Interface	3 x Gigabit LAN	
Radio Chains/Streams	2x2: 2	

HQ , Taiwan www.engeniusnetworks.com	Singapore (+65) 6227 1088 www.engeniustech.com.sg	
Costa Mesa, California, USA (+1) 714 432 8668 www.engeniustech.com	Miami, USA (+1) 305 887 7378 pg.engeniustech.com es.engeniustech.com	EnGenius
Dubai, UAE (+971) 4 357 5599	Eindhoven, Netherlands (+31) 40 8200 888	

Features and specifications subject to change without notice. Trademarks and registered trademarks are the property of their respective owners. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his/her own expense. Prior to installing any surveillance equipment, it is your responsibility to ensure the installation is in compliance with local, state and federal video and audio surveillance and privacy laws.

Version 1.0-03/27/17