AC POWER DISTRIBUTION UNIT, 32A





32A







Circuit Breaker

Safety Shutter TIS Outlet





PDU Product Guide



Surge suppressor (Line suppression)

FEATURES

Applications Provided TIS outlet which is suitable for network equipment, computer,

1> 32A AC Power Distribution Unit

- 3x6mm² with 32A circuit breaker and surge protector for short circuit protection.
- 3m., 5m. and 10m. Power cord with IEC 60309 plug for 12 and 20 outlets.
- 2> 19" Germany Export Rack Socket Made from PC/ABS (UL94V-0), TIS type with embossing trademark.

Manufactured provide

- LED Pilot Lamp and 32A Circuit Breaker w/Guard
- Housing is made from Electro-Galvanized Steel sheet in Light gray or Black paint by Electrostatic powder coating process.
- Mounting bracket for vertical installation in 19" Rack cabinet.
- Manufacturer and Distributor Certified by ISO 9001: 2015.

Technical Specification

Socket Outlet Safety Shutter Socket with L, N and G,

TIS 166-2549

Circuit Breaker w/Guard 32A

Surge Current 6.5KA or 10KA

Input Voltage 220 - 250VAC, 50/60Hz

Max Power 8.000W

Plug Type Power Plug IEC 60309 (32A), IP44

Housing Electro-Galvanized Steel Thickness 0.8mm.

Power Cord VCT-G, TIS 11 Part101-2553

-25°C to +85°C Temperature

ORDERING INFORMATION

Order No.	Description	Figure
G7-00112	AC POWER DISTRIBUTION 12 TIS Outletw/Cable 3 M.	F
	& IEC 60309 Plug W/CB 32A	
G 7-00120	AC POWER DISTRIBUTION 20 TIS Outletw/Cable 3 M.	G
	& IEC 60309 Plug W/CB 32A	

^{*} Black Color : G7-00XXXB

Order Number	Safety Shutter Outlet		Plug Type		Special Function					
	TIS 166-2549	TIS 166-2549 (Black)	TIS 166-2549	Industrial Power Plug IEC60309	Lighting Switch	LED Pilot Lamp	Electronic Circuit Breaker	Circuit Breaker w/Guard	Surge suppressor	L x W x H (cm)
G7-00004	4	22	✓		1	14	1		1	39.2 x 5.8 x 4.45
G7-00006	6		✓		✓	950	1	2	✓	49.5 x 5.8 x 4.45
G7-00008	8	-	✓	-	√	:00	✓		✓	59.5 x 5.8 x 4.45
G7- 00012	12		✓	=	✓	-	✓	D .	✓	78.4 x 5.8 x 4.45
G 7-00020	20		✓	-	✓	1. 1	✓		✓	118 x 5.8 x 4.45
G7-00004B	20	4	✓	=	✓	241	✓	1.91	✓	39.2 x 5.8 x 4.45
G7-00006B	17/1	6	✓	=	1	1.71	✓	22	✓	49.5 x 5.8 x 4.45
G7-00008B		8	✓	Ξ.	✓	-	✓	77	✓	59.5 x 5.8 x 4.45
G7-00012B	727	12	✓	8	✓	12	✓	341	✓	78.4 x 5.8 x 4.45
G7-00020B	3	20	✓	-	✓	188	✓	-	✓	118 x 5.8 x 4.45
G 7-00112	12	-	¥	✓	¥	1	*	✓	✓	87 x 5.8 x 4.45
G 7-00120	20	-		✓	Ē	✓	3	✓	✓	127 x 5.8 x 4.45
G7-00112B		12	*	✓	*	✓	(4)	✓	✓	87 x 5.8 x 4.45
G7-00120B	727	20		✓		✓	200	✓	✓	127 x 5.8 x 4.45