tactio™

Powerline Adapter   CONCERO-85TX4G

85M Powerline Wireless Adapter
Integrated 4 Port 10/100 Switch

- Up to 85Mbps data transfer rate
- Maximum ranges of 200 meters
- Support data transfer rates up to 54Mpbs for wireless network
- 56-bits DES link encryption for security

Enjoy sharing your internet, files, and other network resources with low cost and effectively use of existing resources. tactio™ CONCERO series make it simple to connect your computers, printers, and some other network devices in your place by using existing electrical wiring and outlets, based on the concept of "no new wires". It is a convenience and cost efficient way to create a home or SOHO network especially connecting computers in different rooms without effect cost of regular electric bill, It also reduces your cost of wiring LAN cables for Local Area Network. For wireless users, it reduces problem of no or weak signal area. You can easily combine wiring and wireless solutions by connecting an Access point with a tactio™ powerline adapter in that room. tactio™ CONCERO is easy to install, functional, and nice looking - - perfect for all home and SOHO users.

Technical Specifications

- **Standard**
  IEEE802.3 (10BASE-T)
  IEEE802.3u (100BASE-TX)
  IEEE802.11b/g
  HomePlug 1.0

- **Wireless Features**
  Support 54Mbps Wireless Access Point
  Support 128bits WEP encryption, WPA-PSK, WPA2-PSK, 802.1x
  OFDM: BPSK, QPSK, 16QAM, 64QAM for IEEE802.11g
  DSSS: DBPSK, DQPSK, CCK for IEEE802.11b

- **Powerline Features**
  OFDM (Orthogonal Frequency Division Multiplexing)
  Supports 256/64/16 QAM, DQPSK, DBPSK and ROBO modulation schemes
  4.3MHz – 20.9MHz for frequency band
  56 bits DES encryption for security
  Ranges of 200 meters
  Up to 85Mbps

- **Port**
  Four LAN ports (RJ-45, 10/100Mbps)
  One Power Jack

- **LED Indicator**
  Powerline Status, Wireless and LAN Activity, Power

- **Operating Environment**
  Temperature: 0°C to 50°C, 32°F to 122°F
  Humidity: 10% - 90% (non-condensing)

- **Conformance**
  FCC, CE

tactio™